

Through Beam Sensor



SN2003

Part Number





- Glass Lenses
- Test Input

Technical Data

Optical Data	
Range	20000 mm
Light Source	Red Light
Service Life (T = +25°C)	100000 h
Opening Angle	4 °
Electrical Data	
Sensor Type	Emitter
Supply Voltage	10...30 V DC
Current Consumption (Ub = 24V)	< 20 mA
Temperature Drift	< 10 %
Temperature Range	-25...60 °C
Mechanical Data	
Housing	Plastic
Full Encapsulation	yes
Degree of Protection	IP67
Connection	M12 x 1
Protective Insulation, Rated Voltage	50 V
Connection Diagram No.	703
Control Panel No.	K 3 No3
Suiting Connection Technology No.	2
Suiting Mounting Technology No.	350

These through beam sensors are well suited for use in aggressive industrial environments. The sensor can be checked for correct functioning via the test input. Thanks to their large working range, the devices demonstrate excellent functional reliability in highly contaminated environments.





Legend

+	Supply Voltage +	U	Test Input
-	Supply Voltage 0V	U	Test Input inverted
~	Supply Voltage (AC Voltage)	W	Trigger Input
A	Switching Output (1,2,3...)/NO	O	Analog Output
A	Switching Output (1,2,3...)/NC	O-	Ground for the Analog Output
V	Contamination/Error Output (NO)	BZ	Block Discharge
V	Contamination/Error Output (NC)	AWV	Valve Output
E	Input (analog or digital)	a	Valve Control Output +
T	Teach Input	b	Valve Control Output 0V
Z	Time Delay (activation)	SY	Synchronization
S	Shielding	E+	Receiver-Line
RxD	RS-232 Receive Path	S+	Emitter-Line
TxD	RS-232 Send Path	±	Grounding
RDY	Ready	SnR	Switching Distance Reduction
GND	Ground	USBD+	USB data +
CL	Clock	USBD-	USB data -
E/A	Output/Input programmable	Bus	Interfaces-Bus A(+)/B(-)
	IO-Link	La	Emitted Light disengageable


Wire Colors according to DIN IEC 757

BK	Black
BN	Brown
RD	Red
OG	Orange
YE	Yellow
GN	Green
BU	Blue
VT	Violet
GY	Grey
WH	White
PK	Pink
GNYE	Green Yellow

Complimentary Products

Dust extraction tube STAUBTUBUS-03

Ctrl.Panel Optic



04 = Function Indicator